

IN THE SPECIFICATION:

Please amend the sentences at lines 8 and 9 in the third paragraph on page 6 as follows:

As shown in Figures 7-10, a lip portion 38 thereof is formed at an upper end of each contact prong 36A, 36B, having a sloping lip surface 40 at the bottom adjacent the entry and of recess 28A and a ~~relative~~ relatively blunt top surface ~~42~~ 46 at the end of each contact prong 36A, 36B.

At line 14 in the fifth paragraph on page 6 please change surfaces ~~42~~ to surfaces 41.

Please amend the paragraph beginning at line 8, on page 7 as follows:

The isolator 16 is preferably molded onto the steel rod end 14 as shown in Figures 3 and 10, although it could be separately molded and assembled thereto, ~~which is~~ the rod end 14 formed with a wide groove ~~42~~ 43 into which the material of the isolator 16 extends. The isolator 16 is itself formed with an intermediate groove 45 aligned with the rod groove 43 into which a land 46A, 46B on each housing piece end portion 32A, 32B extends to create a secure interlock by an interference fit between the housing pieces and isolator when the housing pieces are moved to engage the isolator 16 when assembled together which avoids the presence of any looseness or lash.

A land 48A, 48B of each end portion 32A, 32B also projects over a shoulder 50 of the isolator 16 to further strengthen the connection.